



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

RoHS Compliant ✓

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	9/9/11	D.GRIFFIN
B	ECN 5868: ADDED LENGTH 03 M, 075 M	12/1/11	D.FRISIELLO
C	ECN 6451: UPDATED LOGOS, NOTES, AND CHANGED EXPOSED CONN. DIM.	10/10/12	D. DESJARDIN

(2X .463 [11.75] MIN.)


LENGTH



"P1"

"P2"


2X, SERIES "A" USB PLUG CONTACTS: 30 μINCHES GOLD PLATING



2X, MOLDED HOOD AND STRAIN RELIEF PVC, BLACK

ONE 28AWG STRANDED (19X40) TINNED COPPER TWISTED PAIR
 TWO 24AWG STRANDED (42X40) TINNED COPPER CONDUCTORS
 DRAIN WIRE, 28AWG STRANDED (19X40) TINNED COPPER
 OVERALL ALUMINIZED POLYESTER SHIELD PLUS TINNED COPPER BRAID SHIELD
 POLYURETHANE OUTER JACKET, BLACK

MODEL NUMBER	LENGTH METERS [FEET]
CAUAAHFX-03M	.3 [.98]
CAUAAHFX-05M	.5 [1.64]
CAUAAHFX-075M	.75 [2.46]
CAUAAHFX-1M	1.0 [3.28]
CAUAAHFX-2M	2.0 [6.56]
CAUAAHFX-3M	3.0 [9.84]
CAUAAHFX-5M	5.0 [16.41]



NOTES:

- CABLE IS RATED FOR 10,000 BEND CYCLES, MINIMUM
- CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
- CABLE ASSEMBLY SHALL MEET USB 2.0 REQUIREMENTS.
- CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
- CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0%	APPROVALS	DATE		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845
	DRAWN BY D. PARHAM	05/19/2011		CATEGORY
ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 .XX = ±.02 .XXX = ±.005	CHECKED BY D.GRIFFIN	9/9/11	PRODUCT DESCRIPTION	CA,USB A/A HI-FLEX
PROJECTION 	APPROVED BY S.SMITH	9/9/11		
	COLOR VARIATIONS MAY OCCUR	SIZE A	FSCM NO. 43321	DWG. NO. CAUAAHFX
		SCALE: NONE	CAD FILE: CAUAAHFX.SLDDRW	SHEET 1 OF 1