

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS							
REV	DESCRIPTION	DATE	APPROVAL				
Α	REV A DRAWING RELEASED	10/01/2018	BPUCHASKI				
В	ECN 11370 UPDATE JACKET MARKING	09/16/2021	DGUTTADAURO				

#### TOAC5-BLK

TOAC5-BLK CONSISTS OF 1000 FEET OF CONTINUOUS LENGTH BULK CABLE





CAT5e, UTP, OUTDOOR RATED CABLE WITH MESSENGER, 4 TWISTED PAIR 24AWG SOLID-BARE COPPER

#### **NOTES:**

### 1.CONSTRUCTION:

CONDUCTOR: 24AWG SOLID BARE COPPER INSULATION: PE AVERAGE THICKNESS (mm) .205 INSULATION DIAMETER (±.005mm) .91 TWISTED PAIR DIAMETER (±.01mm) 1.92 MESSENGER: GALVANIZED STEEL (mm) Ø1.30

NOM. WALL THICKNESS (mm)
OUTER DIAMETER (±0.10mm)
RIP CORD: YES
NYLON

RIP CORD: YES NYLON

3.PHYSICAL PROPERTIES:

TEMPERATURE RATING -40°C~70°C

FLAMMABILITY TEST IEC-332-1

## 4.PRINT:

VERTICAL 4001453 CETLUS VERIFIED CMX UTP 4PR 24AWG OUTDOOR UV CAT5E 350MHz ANSI/TIA-568.2-D ROHS XXXFT (SEQUENTIAL FOOT MARKERS ON JACKET)

# **5.ELECTRICAL CHARACTERISTICS:**

IMPEDANCE 1.0-350 MHz (Ohms) 100±15
DELAY SKEW (ns/100m) ≤45
PAIR-TO GROUND CAPACITANCE UNBAL. (pF/100m) ≤330
VOLTAGE RATING 60V
MAX. D.C. RESISTANCE 20°C (Ohms/km) 93.8
RESISTANCE UNBALANCES (%) <5

## 6.PACKAGING:

CABLE SHIPPED ON A REEL

REGULATORY COMPLIANCE: CE2011/65/EU(RoHS DIRECTIVE)

### **COLOR CODE**

1)BLUE/WHITE-BLUE

2)ORANGE/WHITE-ORANGE

3)GREEN/WHITE-GREEN

4) BROWN/WHITE-BROWN

	APPROVALS	DATE	_				
UNLESS OTHERWISE SPECIFIED,	DRAWN BY		<b>18</b> —			Global 50 HIC	SH STREET
DIMENSIONS ARE IN INCHES [mm]	BPUCHASKI	10/01/2018	Connectivity NORTH ANDOVER, MA				
, ,	CHECKED BY					O	1845
OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / - 0	DFRISIELLO	10/01/2018	CATEGO	DV			
>12 [305] - 60 [1524] = +2 [51] / -0	APPROVED BY	10/01/2018	CAIEGO	KI	-	TELECONA/NAODIII AD	
>60 [1524] - 120 [3048] = +4 [102] / -0 >120[3048] - 300[7620] = +6 [152] / -0	DGUTTADAURO		TELECOM/MODULAR				
>300[7620] = +5% / -0%	-		PRODUCT DESCRIPTION				
ALL OTHER DIMENSIONAL TOLERANCES:	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		I ROBOCI DESCRI HOIV				
X = .2 [5.08]			Cat5e UTP 24SLD Aerial OSP PE BLK 1KFT				
.XX = .02 [.51] .XXX = .005 [.13]			Calob off 2-5EB / total Col 1 E BER 11(1)				
						1	
PROJECTION	COLOR VARIATIONS MAY OCCUR		SIZE	FSCA	A NO.	DWG. NO.	REV.
( <del>+</del> ) + - +			Α	433	321	TOAC5-BLK	B
<b>4</b> —			SCALE:	1:4	CAD F	FILE: TOAC5-BLK.SLDDRW	SHEET 1 OF 1