

## 20"x16"x11" Weatherproof Industrial Enclosure Model: NB201611

### Applications

- Wireless LAN WiFi equipment installations
- Indoor and outdoor installations
- Industrial control equipment installations
- High temperature or corrosive environments
- Hydraulic or pneumatic control installations

### Features

- Molded fiberglass reinforced polyester (FRP) Material
- Fully gasketed lid
- Stainless steel lockable latches
- UL/CSA/NEMA/IP rated
- Integral mounting flange



### Description

The NB series is a UL/CSA® Listed rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from molded halogen free self extinguishing fiberglass reinforced polyester (FRP), it is well suited for high temperature or corrosive environments. The integral mounting flange allows it to be wall mounted as well as on a flat surface without the need for extra mounting hardware. The fully gasketed lid features a stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. The light grey color of the NB series is cleaner, cooler and aesthetically pleasing. Users can enjoy the physical benefits of better heat reflection and better UV resistance due to the lighter color. The contoured body provides an attractive and contemporary appearance.

The NB series is ideal for custom applications, which may require special modifications to the enclosure. Contact L-com with your custom requirements and let us provide it for you. Integral mounting stand-offs inside the enclosure can be used for mounting plates. Blank and custom mounting plates are available from L-Com.

Mushroom Head Cover



Ribbed Cover Corners



Molded Mounting Flanges



## Specifications

<b>Enclosure Material</b>	Halogen free, self extinguishing fiberglass reinforced polyester (FRP)
<b>Enclosure Color</b>	Light Grey (RAL7035)
<b>Weight</b>	19.75 lbs (8.95 kg)
<b>Outside Dimensions (max)</b>	17.3 x 21.3 x 11.6 in (440 x 541 x 294mm)
<b>Inside Dimensions</b>	20.0 x 16.0 x 11.1 in (506 x 404 x 283mm)
<b>Temperature Ratings</b>	Continuous: -58°F to 302°F (-50°C to 150°C) Momentary exposure up to 392°F (200°C).
<b>UL and CSA Approved</b>	Yes
<b>RoHS Compliant</b>	Yes
<b>NEMA Ratings*</b>	Type 3, 3R, 3S, 4, 4X, 12 and 13
<b>IEC 529 Ratings*</b>	IP66-11

\*Ratings prior to modifications

